



## PX-140S

PX Pressure Exchanger® Energy Recovery Device

# PX-140S

## PX Pressure Exchanger® Energy Recovery Device



The PX-140S Pressure Exchanger is part of ERI®'s 4S-Series dual energy recovery device product line. 4S Series PX® devices are ideal for small to medium-size SWRO applications. The PX-140S is a dual rotor unit designed to handle brine flows from 20 to 32 m<sup>3</sup>/hr (90 to 140 gpm), corresponding to permeate flows of 16 to 26 m<sup>3</sup>/day (70 to 114 gpm) when operating at 45% recovery. These units are typically used in parallel to service larger systems.

The 4S-Series incorporates design improvements that increase capacity and improve durability.

### PREMIUM QUALITY AND ADVANCED TECHNOLOGY OVER ANY OTHER ERD

PX Pressure Exchanger (PX®) technology greatly reduces water production costs by up to 60%. Industry experts designed and tested PX devices in seawater and brine environments. The PX units are encased in industry standard 4" diameter housings proven to provide extended field service life in SWRO applications.

Since its introduction in 1997, PX technology has emerged as the industry standard solution for SWRO desalination. PX devices installed for several years have proven the endurance of the ceramic construction by requiring no routine maintenance when operated for tens of thousands of hours in tough seawater environments. With over 120 combined years of industry experience, ERI has assembled a technical services and support

team with exceptional knowledge of RO systems. Our team members have consulted with numerous SWRO operators, aiding in design review, on-site training and support.

### HIGH CONSTANT EFFICIENCY

The ERI PX device achieves real energy transfer efficiencies up to 98%, making it the most efficient ERD technology available today. The positive displacement mechanism employed by the PX device provides constant ultra high efficiencies over a broad range of flows and pressures. ERI guarantees PX device efficiency to be greater than 95% for most SWRO applications regardless of salinity, temperature or recovery rate variations. This characteristic *differs* from centrifugal devices whose performance declines as flows and pressures shift away from device best efficiency points. High and constant efficiency are significant operating cost advantages over other energy recovery devices on the market.

### CERAMIC COMPONENTS

At the core of the PX device is a cartridge made of tough, engineered corundum (aluminum oxide). This ceramic material is unaffected by chemicals and will not corrode. Its properties are similar to that of sapphire and its hardness exceeds that of many stainless steels by a factor of three. In fact, most PX units taken apart for inspection after years of service exhibit no evidence of wear or deterioration whatsoever.

### QUALITY DESIGN & CONSTRUCTION

Due to harsh conditions and continuous service requirements in SWRO plants, material specification, fabrication and assembly are critical to ensuring ERI's products perform consistently and reliably. Precise machining, inspection and performance testing are conducted. ERI's Engineering and Manufacturing departments work closely to maintain tight control and assure quality. Because of proven reliability and maintenance free performance, the ERI PX is one of the few rotating devices in the world that is backed by a **free five year warranty**.

### PROVEN RELIABILITY AND EXPERIENCE

PX technology has emerged as the industry standard for projects of all sizes; primarily due to the PX device's consistent delivery of energy and maintenance savings – with no excuses about changes in original design envelopes. Over 80 OEMs worldwide have stan-





standardized on PX technology with installations from small to medium (in practically every part of the world), to the world's largest desalination plants in Algeria, Australia, China, India, Mexico, Spain, along the Mediterranean Sea and the Middle East.

### LOWEST LIFECYCLE COSTS

ERI's global install base saves real money compared to older energy recovery technologies such as Pelton wheels, Francis turbines and turbo chargers.

- Over \$352 Million per year in energy saved
- Up to 98% efficient
- Proven SWRO power consumption as low as 1.6 kWh/m<sup>3</sup> \*
- Real power savings of over 500 MW worldwide

### WORLD-WIDE REFERENCES

ERI has 10 times more operating experience than the next manufacturer of isobaric energy recovery devices.

- Millions of unit hours of proven reliability
- Over 80 OEM's using PX devices with over 6,000 units sold or contracted worldwide
- More than 5,200,000 m<sup>3</sup>/day of capacity installed or under construction
- Multiple 10,000 m<sup>3</sup>/day trains operating for more than three years
- Standard 5 year warranty

### SIMPLE DESIGN & EASE OF USE

PX technology offers the simplest approach to isobaric energy recovery available today; only one moving part and no scheduled maintenance. Its ease of use with no artificial intelligence or adaptive control schemes as well as fail-safe design features makes the PX device easy at startup and shutdown.

- Constant high efficiency over entire operating range
- One moving part
- Zero scheduled maintenance
- Smallest installed footprint when compared to other isobaric ERDs
- No pulsation, valves, pistons or timers

### MATERIALS


- Alumina Ceramic
- Fiberglass Reinforced Polymer (FRP) internal components
- Industry Standard FRP housing
- 254 SMO<sup>®</sup>, AL-6XN<sup>®</sup> or equivalent high-pressure fittings
- Flexible coupling connections for easy installation

\*ADC

AL-6XN<sup>®</sup> is a registered trademark of Allegheny Ludlum Corp.  
254 SMO<sup>®</sup> is a registered trademark of Avesta Sheffield AB.



**External Dimensions and Piping Details**



Capacity m <sup>3</sup> /hr (gpm)	Connections (6) inches				Shipping Dimensions mm (inches)	Shipping Weight kg (lbs)
	LP IN	LP OUT	HP IN	HP OUT		
21 - 32 (90 - 140)	1.5	2.0	2.0	1.5	1168 x 330 x 279 (46 x 13 x 11)	49 (108)

See ERI Document Number 40012 current revision for assembly dimensions and component bill of materials.

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWINGS IS THE SOLE PROPERTY OF ENERGY RECOVERY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF ENERGY RECOVERY, INC. IS PROHIBITED

©2009, ENERGY RECOVERY, INC.

Making Desalination Affordable®



**Energy Recovery, Inc.**  
 1908 Doolittle Drive  
 San Leandro, CA 94577  
 TEL +1 (510) 483-7370  
 FAX +1 (510) 483-7371  
 EMAIL info@energyrecovery.com  
 WEB www.energyrecovery.com



©Energy Recovery, Inc. 2009 All Rights Reserved.  
 Design and specifications subject to change without prior notice.  
 Doc. No. ERI-PB102ED 2009-02